



ELDOOR TZ


Tangential air curtains



FEATURES

- 3 sizes: 90, 120 or 150 cm width
- Air velocity 11 m/s
- Installation height: 2,3÷3 m
- 2 speeds (with LED signal)
- Remote controller included
- Single-phase power supply
- Stainless steel and varnished metal housing
- Airflow orientation through deflectors
- Can be coupled with the door magnetic contact (supplied as accessory) for automatic on/off running
- High efficiency and silent running
- Easy to install thanks to the fixing bracket (included)
- Inlet front side allows an installation close to the ceiling
- Supplied with connexion cable and plug (TYPE L, 3 poles, 10A)

INCLUDED



REMOTE CONTROLLER

PERFORMANCE

CODE	UNIT OF MEASUREMENT	MODELS		
		ELDOOR 900 TZ 4BA0000	ELDOOR 1200 TZ 4BA0001	ELDOOR 1500 TZ 4BA0002
Voltage - Frequency	V - Hz	230-50	230-50	230-50
Size (Width)	cm	90	120	150
Impeller diameter	mm	120	120	120
Installation height	m	2.3 - 3	2.3 - 3	2.3 - 3
Electric power	W	150	180	220
Air velocity	m/s	11	11	11
Airflow	m ³ /h	1200	1700	2100
Sound levels	db(A)	45	47	47
Dimensions (L x h x w)	mm	900x220x195	1200x220x195	1500x220x195
Weight	kg	13	16	20



ELDOOR CF


Centrifugal air curtains



FEATURES

- 3 sizes: 90, 120 or 150 cm width
- Air velocity 14,5 m/s
- Installation height: 3÷3,5 m
- 2 speeds (with LED signal)
- Remote controller included
- Single-phase power supply
- Stainless steel and varnished metal housing
- Airflow orientation through deflectors
- Can be coupled with the door magnetic contact for automatic on/off running (supplied as accessory)
- High efficiency and silent running
- Easy to install thanks to the fixing bracket (included)
- Inlet front side allows an installation close to the ceiling
- Supplied with connexion cable and plug (TYPE L, 3 poles, 10A)

INCLUDED



REMOTE CONTROLLER

PERFORMANCE

CODE	UNIT OF MEASUREMENT	MODELS		
		ELDOOR 900 CF 4BA0010	ELDOOR 1200 CF 4BA0011	ELDOOR 1500 CF 4BA0012
Voltage - Frequency	V - Hz	230-50	230-50	230-50
Size (Width)	cm	90	120	150
Impeller diameter	mm	120	120	120
Installation height	m	3.0 - 3.5	3.0 - 3.5	3.0 - 3.5
Electric power	W	220	275	330
Air velocity	m/s	14.5	14.5	14.5
Airflow	m ³ /h	1020	1360	1700
Sound levels	db(A)	44	45	48
Dimensions (L x h x w)	mm	960x230x212	1200x230x212	1500x230x212
Weight	kg	16	19	24