



### TECHNICAL SPECIFICATION

Airflow (m <sup>3</sup> /h)	190
RPM	14.000 - 19.000
Air velocity (Km/h)	140 - 205
Air temperature (l)	45°
Motor Power (W)	200 - 1.000
Consumption (A)	2,4 - 5,2
Heating element power (W)	0 - 600 (interruttore on/off)
Noise level Lp (dBA)	65 - 73
Voltage (V)	220 - 240
Frequency (Hz)	50 / 60
Electric insulation	Class I
Weight (Kg)	5,6
Dimensions (cm)	26,5 x 42 x 17
Protection	IP23

<sup>(1)</sup> The air temperature can be increased to 45°C via an on/off switch connected to a small resistance of 400 W.

### FEATURES

- High speed airflow (140-205 Km/h) for a quick dry.
- Compact, AISI 304 steel one-piece cover with white epoxy coated and anti-scratch paint, 1,5 mm thick.
- Axial impeller in self-extinguishing PP UL 94-V0
- Adjustable power from 14.000 to 19.000 RPM
- Fitted with a security system that switches off the fan after 60 sec of continuous use
- Motor with thermal protection
- Safe flexible duct, thermal protected.
- Adjustable air temperature up to 45°C via an on/off switch connected to a small resistance.
- White ABS handset with a thermal protection inside.
- Comply with EN 60335-1, 60335-2-23, EN 50366, EMC 2014/30/UE and LVD 2014/35/UE.



- Antivandal with cover in **INOX AISI 304**
- Compact and essential design
- Safe and efficient
- Perfect thermal insulation