



VOLCANO R

Industrial






PERFORMANCE

CODE	MODEL	V at 50 Hz	kW		A	DIMENSIONS L x p x h	WEIGHT (Kg)
			MIN	MAX	MAX		
4TV3011	VOLCANO R 3300	230	1,63	3,3	14,3	250 x 250 x 420	5
4TV5011	VOLCANO R 5000	400	2,5	5	7,2	250 x 250 x 420	8

FEATURES

- Heaters ideally suited for heating small and medium sized industrial premises
- Manufactured in rugged steel cabinet with strong safety insulated handles
- Encapsulated stainless steel heating elements that are extra-insulated from the cabinet
- Provided with safety thermostat which guards against overheating and ensures that fire hazard does not arise
- 2 models: 3,3 or 5 kW
- Provided with room thermostat to maintain the desired temperature
- Selectable heating effect, between 1/2 and 1/1 through the selector switch
- The 5 kW model is provided with a CEE plug of 16A, 5 poles, IP44 while the 3kW model is provided with a Schuko plug of 16A IP44.
- Wall mounting kit available as an accessory



VOLCANO PRO

Industrial



PERFORMANCE

CODE	MODEL	V at 50 Hz	kW		A	m³/h	DIMENSIONS L x p x h	WEIGHT (Kg)
			MIN	MAX	MAX			
4TV6011	VOLCANO PRO 6000	400	3	6	10	1600	340 x 390 x 510	7
4TV9011	VOLCANO PRO 9000	400	4,5	9	13	1700	340 x 390 x 510	7,5

FEATURES

- Heaters ideally suited for heating medium sized industrial premises
- 2 models: 6 or 9 kW
- Very compact and unique dimension for both models
- Housing in steel sheet
- Provided with delay start and delay stop functions, settable on the panel
- Provided with a cooling down post ventilation function (max 10 minutes)
- Provided with a CEE plug of 16A, 5 poles, IP44
- Wall mounting kit available as an accessory

